

codeaa

```
create database pravindb;
```

```
show databases;
```

```
use pravindb;
```

```
create table emp(
eid int not null unique,
ename varchar(20),
gender char
);
```

```
desc emp;
```

```
insert into emp values
```

```
(1,"pravin",'M'),(2,"sai",'M'),(3,"keshav",'M'),(4,"prashant",
```

```
select * from emp_new;
```

```
select eid,ename from emp;
```

```
alter table emp drop gender;
```

```
alter table emp add salary int default 10000,add city varchar(20) default 'mumbai';
```

```
alter table emp rename to emp_new;
```

```
alter table emp_new rename column city to location;
```

```
alter table emp_new modify salary varchar(20) after eid;
```

```
alter table emp_new modify salary varchar(20) after location;
```

```
select * from emp_new;
```

```
select * from emp_new limit 2 offset 3;
```

```
update emp_new set location ='rajasthan' where eid in (1,2);
```

```
update emp_new set location ='gujarat' where eid in (3,4);
```

```
update emp_new set location ='kholpur' where eid in (5);
```

```
update emp_new set salary =12000 where eid in (1,2);
```

```
update emp_new set salary ='18000?' where eid in (3,4);
```

```
update emp_new set salary ='22000?' where eid in (5);
```

```
select salary ,ename from emp_new <
```



[Read More](#)